

CXW SERIES



- Economical support for heavy conduit, pipe, and equipment
- Versatile, ideal for hundreds of applications
- Built to last UV resistant for tough outdoor conditions
- Designed for heavy-duty rooftop applications
- Suitable for most types of roofing materials and flat surfaces
- Accepts screw fasteners for I-hole or 2-hole straps/clamps (straps and clamps are not included)

LIMITED LIFETIME WARRANTY

MAY QUALIFY FOR L.E.E.D CREDITS

RECOMMENDED SPACING: REFER TO LOCAL CODE




100%
RECYCLED RUBBER

CONSULT WITH A ROOFING CONSULTANT FOR ALLOWABLE LOADS.

SKU	HEIGHT	WIDTH	LENGTH	WEIGHT	MAX. LOAD
CXWI2	2.5" (64мм)	12" (305мм)	12" (305мм)	9.2 LBS	IOOO LBS PER I2" LENGTH
CXW24	2.5" (64мм)	12" (305мм)	24" (610мм)	18.4 LBS	
CXW36	2.5" (64мм)	12" (305мм)	36" (914мм)	27.6 LBS	
CXW48	2.5" (64мм)	12" (305мм)	48" (1219мм)	36.7 LBS	
CXW60	2.5" (64мм)	12" (305мм)	60" (1524мм)	45.9 LBS	
CXW72	2.5" (64мм)	12" (305мм)	72" (1829мм)	55.I LBS	

Note: All measurements may vary by +/- 3%



MATERIALS

BASE: IOO% RECYCLED RUBBER UV RESISTANT



info@clearline.ca I-866-444-0009 www.c-port.net

Revision Date: 05/2025